



SIDEX s.r.l.

SERVIZI SPECIALIZZATI IN PRODOTTI SIDERURGICI

Tolerances for flat drawn bars
ACC UNI EN 20286 (h.11)

on WIDTH	TOLERANCE	
	mm	mm
≤ 18	+0	-0.11
$> 18 \leq 30$	+0	-0.13
$> 30 \leq 50$	+0	-0.16
$> 50 \leq 80$	+0	-0.19
$> 80 \leq 100$	+0	-0.22
$> 100 \leq 150$	+0.50	-0.50
$> 150 \leq 200$	+1.00	-1.00
$> 200 \leq 300$	+2.00	-2.00
$> 300 \leq 400$	+2.50	-2.50

on THICKNESS	TOLERANCE	
	mm	mm
$> 3 \leq 6$	+0	-0.075
$> 6 \leq 10$	+0	-0.090
$> 10 \leq 18$	+0	-0.11
$> 18 \leq 30$	+0	-0.13
$> 30 \leq 50$	+0	-0.16
$> 50 \leq 60$	+0	-0.19
$> 60 \leq 80$	+0	-0.30
$> 80 \leq 100$	+0	-0.35

On LENGTH: mm. 3000: - 0/+10%
mm. 6000: - 0/+10%
fixed lengths upon request.